

When IoT Keeps People in the Loop: A Path Towards a New Global Utility

Journal:	<i>IEEE Communications Magazine</i>
Manuscript ID	COMMAG-17-00018.R3
Topic or Series:	Open Call Article
Date Submitted by the Author:	11-Sep-2018
Complete List of Authors:	Petrov, Vitaly; Tampere University of Technology, Electronics and Communications Engineering Mikhaylov, Konstantin; University of Oulu, Centre for Wireless Communications Moltchanov, Dmitri; Tampere University of Technology, Department of Electronics and Communications Engineering Andreev, Sergey; Tampere University of Technology, Department of Electronics and Communications Engineering Fodor, Gabor; Ericsson Research, Wireless Access Networks Torsner, Johan; Ericsson Research, Telecommunications Yanikomeroglu, Halim; Carleton University, Systems and Computer Engineering Juntti, Markku; University of Oulu, Centre for Wireless Communications Koucheryavy, Yevgeni; Tampere University of Technology, of Electronics and Communications Engineering
Key Words:	Internet of Things, Human-in-the-Loop, User-in-the-Loop, People-centric



1
2
3
4 **When IoT Keeps People in the Loop: A Path Towards a New Global Utility**
5

6 Vitally Petrov, Konstantin Mikhaylov, Dmitri Moltchanov, Sergey Andreev, Gabor Fodor, Johan Torsner,
7 Halim Yanikomeroglu, Markku Juntti, and Yevgeni Koucheryavy
8

9 *Dear Editors,*

10
11 *Thank you very much for sharing your expert opinions on our work. We really appreciate the time and*
12 *effort taken in reviewing this submission. As a result, we are confident that our paper has benefited*
13 *considerably from your constructive comments and suggestions, which were extremely helpful in*
14 *improving the quality of this manuscript.*

15
16
17 *In this minor revision, we have made certain that our revised article is fully compliant with ALL of the*
18 *effective IEEE Communications Magazine guidelines.*

19
20 *The focused point-to-point answers to the review comments follow, where the feedback from the Editor is*
21 *given in regular font, while our corresponding comments are highlighted in **bold font**.*

22
23
24
25
26 Guest Editor

27 - Although, the reviewers are satisfied with the made changes. However, a very high similarity (87%) is
28 observed with the archived version of the almost same manuscript submitted by the same authors. The
29 authors might refer to

30 http://www.ieee.org/publications_standards/publications/journmag/ieee_publishing_policy.pdf

31 3. Policy on Electronic Posting

32 Authors submitting manuscripts for review should be aware of the IEEE policy on “Electronic
33 Information Dissemination”. The policy applies to authors who post part or all of a submitted manuscript
34 on a Web site. The policy is found in the Publications Services and Products Board (PSPB) Operations
35 Manual, in Sections 8.1.9A and 8.1.9B, as follows:

36 B. ELECTRONIC REPRINTS

37 Upon submitting an article to the IEEE for review and possible publication, the author must add the
38 following notice to the first screen of any of his/her previously posted electronic preprint versions of this
39 paper:

40 “This work has been submitted to the IEEE for possible publication. Copyright may be transferred
41 without notice, after which this version may no longer be accessible.”

42
43
44
45
46 **We are really grateful to the Guest Editor for this important reminder. In this revision round, the**
47 **mentioned archived version of our article available at <https://arxiv.org/abs/1703.00541> has been**
48 **updated. Particularly, the required notice (“This work has been submitted to the IEEE for possible**
49 **publication. Copyright may be transferred without notice, after which this version may no longer**
50 **be accessible.”) has been added to the initial page of the posted electronic preprint (both to the**
51 **preprint summary and the first page of the preprint itself).**

52
53
54 **We have also carefully double-checked the rest of the IEEE Publishing Policy to ensure that our**
55 **revised article is fully compliant with it.**
56
57
58
59
60

1
2
3
4 AEiC

5 - Revision (last chance) should comply with all the guidelines
6 <https://www.comsoc.org/commag/paper-submission-guidelines> and
7 http://www.ieee.org/publications_standards/publications/journmag/ieee_publishing_policy.pdf ;
8 A standalone (separate from response letter) version of the manuscript should be provided for compliance
9 checking.
10
11

12 **We do appreciate receiving this summary of the IEEE Communications Magazine guidelines. In**
13 **this revision round, we have ensured that our updated article is fully compliant with ALL of the**
14 **effective guidelines, particularly:**
15

- 16 1. **The length of the article (introduction through conclusions, excluding figures, tables, and**
17 **captions) is less than 4500 words. The length of each author’s bio is less than 75 words. For**
18 **convenience, find enclosed a separate .docx file to confirm the word count (4453 words).**
- 19 2. **The mathematical content is kept to minimum. There are no equations in our article.**
- 20 3. **There are 5 figures (no sub-figures) and 1 table, thus making it 6 items in total.**
- 21 4. **There are 15 archival references, each of them complete with publication name/title, year,**
22 **volume, issue, and page numbers.**
- 23 5. **Following IEEE publishing policy, a preprint of our article at <https://arxiv.org/abs/1703.00541>**
24 **is supplemented with the following notice in the initial page of the document:**
25
26

27 “This work has been submitted to the IEEE for possible publication. Copyright may be
28 transferred without notice, after which this version may no longer be accessible.”
29

30 The notice is present in both the first page of the preprint and the preprint summary.
31

32 A standalone version of the manuscript has also been uploaded for compliance checking.
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

When IoT Keeps People in the Loop: A Path Towards a New Global Utility

Vitaly Petrov[†], Konstantin Mikhaylov, Dmitri Moltchanov, Sergey Andreev, Gabor Fodor,
Johan Torsner, Halim Yanikomeroglu, Markku Juntti, and Yevgeni Koucheryavy

Abstract—While the Internet of Things (IoT) has made significant progress along the lines of supporting individual machine-type applications, it is only recently that the importance of people as an integral component of the overall IoT infrastructure has started to be fully recognized. Several powerful concepts have emerged to facilitate this vision, whether involving the human context whenever required or directly impacting user behavior and decisions. As these become the stepping stones to develop the IoT into a novel people-centric utility, this paper outlines a path to materialize this decisive transformation. We begin by reviewing the latest progress in human-aware wireless networking, then classify the attractive human-machine applications and summarize the enabling IoT radio technologies. We continue with a unique system-level performance characterization of a representative urban IoT scenario and quantify the benefits of keeping people in the loop on various levels. Our comprehensive numerical results confirm the significant gains that have been made available with tighter user involvement, and also corroborate the development of efficient incentivization mechanisms, thereby opening the door to future commoditization of the global people-centric IoT utility.

I. INTRODUCTION AND VISION

The Internet of Things (IoT) has undergone a fundamental transformation in recent decades: departing from the legacy radio frequency identification (RFID) technology of the 1980s and the wireless sensor networks of the 1990s, which were essentially siloed “connectivity islands” with limited interoperability, to its present form, which is becoming increasingly interconnected and heterogeneous. Today’s IoT is already a fusion of numerous networked tools and appliances, equipped with advanced computational intelligence and rich communication capabilities. More broadly, the principles of contemporary IoT overlap with and permeate many adjacent domains, including mobile and pervasive computing, as well as robotics and cyber-physical systems – with applications ranging from smartphone-based social networking that reduces traffic and pollution in cities to mission-critical industrial automation that monitors and actuates over factory processes [1].

Beyond legacy embedded systems with constrained applicability, the emerging IoT solutions are becoming more open and integrated by adaptively combining sensors and actuators with actionable intelligence for automatic monitoring and control [2]. However, as a multitude of interconnected and intelligent machines communicate with each other and

autonomously adapt to changing contexts without user involvement, the fact that present technology is made by humans and for humans is often overlooked [3]. Indeed, modern IoT systems are still widely unaware of the human context and instead consider people to be an external and unpredictable element in their control loop. Therefore, future IoT applications will need to intimately involve humans, so that people and machines could operate synergistically. To this end, human intentions, actions, psychological and physiological states, and even emotions could be detected, inferred through sensory data, and utilized as control feedback.

This concept, which is known as human-in-the-loop (HITL), becomes a logical next step toward truly social computing and communication in smart cities [4]. HITL opens the door to next-generation people-oriented IoT platforms, which are aware of the people context, mobility, and even mood, thus having more efficient and intuitive manipulation [5]. As users increasingly interact with such human-aware HITL systems, they may also become directly influenced by the control-loop decisions, thereby closing the loop [6]. In fact, people may receive control input from the system in the form of suggestions and incentives (or even penalties) to diverge from their default behavior. Accordingly, human behavior may be impacted in either space (for example, the users are encouraged to move to a less congested location) or time (for example, the users are convinced to reduce their current data demand in case the network is overloaded); this is known as the “user-in-the-loop” (UIL) [7].

With UIL, often referred to as “layer 8”, the space-time user traffic demand may be shaped opportunistically and better matched with the actual resource supply from the people-centric wireless system. While HITL involves the user whenever human participation is desired or required and UIL extends the user’s role beyond a traffic-generating and traffic-consuming black box, these trends must account for the fact that people are, in essence, walking sensor networks [8]. Indeed, a wide diversity of user-owned companion devices, such as mobile phones, wearables, connected vehicles, and even drones may become an integral part of the IoT infrastructure. Hence, they can augment a broad range of applications, in which human context is useful, including traffic planning, environmental monitoring, mobile social recommendation, and public safety, among others. Therefore, we envision that – in contrast to past concepts where the user only assists the network to receive better individual service – future user equipment will truly merge with the IoT architecture to form a deep-fused human-machine system that efficiently utilizes the complementary nature of human and machine intelligence.

Should the IoT keep people in the loop, it has the potential to evolve into an integrated multi-tenant system-of-systems that may form novel, unprecedented services [9]. For instance,

V. Petrov, D. Moltchanov, S. Andreev, and Y. Koucheryavy are with the Laboratory of Electronics and Communications Engineering, Tampere University of Technology, Finland.

K. Mikhaylov and M. Juntti are with the Centre for Wireless Communications, University of Oulu, Oulu, Finland.

H. Yanikomeroglu is with the Department of Systems and Computer Engineering, Carleton University, Canada.

G. Fodor is with Ericsson Research and Wireless@KTH, Sweden.

J. Torsner is with Ericsson Research, Finland.

This work was supported by the Academy of Finland and by the project TAKE-5: The 5th Evolution Take of Wireless Communication Networks, funded by Tekes. [†]V. Petrov is the contact author: vitaly.petrov@tut.fi

the underlying people-centric sensor and actuator network may act as a utility – similar to electricity and water – creating important usable knowledge from vast amounts of data. Facilitated by this new global utility, different IoT devices and networks that previously had nothing to do with each other may discover and start talking to one another, thereby augmenting the current talk-by-design approaches. While the existing studies primarily focus on how the IoT can serve humans in various scenarios [2], [10], in this work we maintain that people can also assist the IoT in its daily tasks, thus closing the loop. This proposed vision renders the next-generation IoT as a genuinely multi-user, multi-tenant, and multi-application platform that can be materialized in the near future by relying on the emerging IoT radio technologies.

Following our offered vision, this article reviews and classifies the people-centric applications related to the long-range radio solutions. We then describe and compare the prominent IoT-enabling radio access technologies (RATs), namely, SIGFOX, LoRaWAN, Wi-Fi HaLow, and NarrowBand IoT. Further, we present a case study for the people-centric IoT system, which investigates how the listed RATs respond to the representative human involvement models and quantify the resultant system-wide benefits. We finally discuss attractive incentivization mechanisms for the IoT to keep its users in the loop, thus aiming for a synergy between the human-centric and the IoT-centric segments of the future Internet.

II. ENVISAGED PEOPLE-CENTRIC IOT APPLICATIONS

In light of the above, a contemporary perspective on the IoT expects it to soon become “the infrastructure of the information society”. The very capable machines, ranging from sensors to vehicles, are already assisting humans in their daily lives. Explosive growth in the population of such connected objects leads to complex human-machine interactions that become increasingly frequent, facilitated by the HITL and UIL concepts. As these interactions intensify, many categories of people-centric IoT services emerge and are expected to be deployed over the following years:

- *Intention- and mission-aware services.* These services primarily reflect user’s current intention or desire and assist by enabling, for example, situation-aware smart commuting for pedestrians, cyclists, and drivers of scooters, trucks, and other vehicles. This group of applications can help people in a variety of use cases, from highlighting the nearest available parking space on a vehicle’s head-up display in urban areas to status reporting on a display or augmented reality (AR) glasses in challenging environments, such as mines, construction sites, etc.
- *Location- and context-aware services.* Another group of services is formed by location- and context-aware applications, such as those communicating alerts from environmental sensors (for example, “put on/take off your mask” when entering/leaving a polluted area). Many more of these services are envisioned to be deployed in the coming years, such as identifying slippery floors and low ceilings, notifying about forgotten trash when a user is about to leave the house, and many other examples.




Fig. 1. Consumer and industrial contexts of people-centric IoT applications.

- *Condition- and mood-aware services.* A deeper level of IoT penetration into people’s lives can be achieved by integrating city/area infrastructure with personal medical and wellness devices. For instance, dietary restrictions could be applied on a menu when ordering food or a squad leader may be advised to give a break to a worker whose blood pressure has recently gone up.

Summarizing the above examples of services, we note that depending on the environment the set of requirements and challenges to implement a particular application may vary considerably. To further offer a challenges-based grouping, we propose to differentiate between two major contexts: consumer and industrial (see Fig. 1). The former is characterized by the presence of numerous devices that are heterogeneous in terms of their communication means and ownership. Therefore, the major challenge in this context is to provide sufficient *scalability* of the deployed connectivity solution. On the contrary, the latter context is more challenging in terms of maintaining communication *reliability* due to more difficult propagation environments. At the same time, the system operator has more control over device population in such areas.

We continue by addressing how people-centric IoT applications are to be engineered, that is, which radio technologies need to be employed in particular scenarios and how to ensure their suitability for the target operating conditions.

III. REVIEW OF WIRELESS CONNECTIVITY OPTIONS

Inspired by the above use cases, we review the contemporary IoT radio access technologies and analyze them through the prism of their applicability for HITL applications. Fig. 2 brings together the major characteristics of the considered RATs.

1) *Current technology diversity:* The demand for developing RATs that focus specifically on the needs of machines was commonly understood in the mid to late 2000s. The low power consumption, affordable cost, high communication range, and capability to handle massive deployments of infrequently transmitting devices became the major requirements for these new solutions, which can be collectively referred to as Low-Power Wide-Area Networks (LPWANs). Development




Fig. 2. Key characteristics of candidate radio technologies for advanced human-machine interaction.

of such technologies progressed in parallel within leading standardization bodies, including IEEE, ETSI, and 3GPP.

This resulted in the sheer diversity of today's LPWAN options, which comprise a number of standardized solutions. Across this diversity, the paths taken by the technology developers differ substantially. To offer illustrative examples, we consider two emerging LPWAN solutions, namely, SIGFOX and LoRaWAN [11]. Both technologies operate in the sub-GHz license-exempt industrial, scientific, and medical (ISM) frequency bands and employ ALOHA-based channel access with frequency hopping, which places them under severe duty cycle restrictions. Topologically, both alternatives adhere to a cellular-like structure.

The SIGFOX solution operates with ultra-narrow band signals: 100 Hz using Binary Phase-Shift Keying modulation and 600 Hz using Gaussian Frequency Shift Keying modulation for uplink and downlink, respectively. Some limitations of this technology are harsh restrictions on the application payload of a radio frame (i.e., 12 bytes at most), the single modulation and coding scheme (MCS), and the limitation on the number of packets that can be sent to and from a device per day to 4 and 140, respectively. Today's SIGFOX installation base exceeds 2.5 million devices.

In contrast to SIGFOX, LoRaWAN supports multiple MCSs. The mandatory MCSs are based on the Semtech's proprietary LoRa spread spectrum modulation derived from the chirp spread spectrum modulation. The number of chirps to carry a single bit as well as the bandwidth of the channel that affects the duration of a single chirp can be adjusted to trade the on-air time for the transmission range. There are currently several commercial deployments of LoRaWAN with the overall number of chips in excess of 5 million.

2) *Machines talk Wi-Fi*: The path followed by the IEEE 802.11 community is substantially different. The work on IEEE 802.11ah standard (also known as Wi-Fi HaLow) has approached its final stage and early chipsets implementing this technology are already announced. The solution targets the "high-end" devices with demanding performance requirements in terms of throughput and latency. To this end, 802.11ah delivers a non-backward compatible communication technology in the sub-1 GHz ISM band, which is based on orthogonal frequency division multiplexing (OFDM) and features several

dozens of different channel bandwidths as well as modulation and coding options. Wi-Fi HaLow does not have any large commercial installations yet, as the technology has recently entered the testing phase.

One of the intrigues that remain today is how close the relationship between the HaLow and the conventional Wi-Fi systems will be. That is, whether HaLow continues on its own or be merged with the traditional Wi-Fi to form dual-mode devices similar to Bluetooth Smart: for example, dual technology enabled access points or Wi-Fi HaLow access points combined with a Wi-Fi client to be used in a smartphone.

3) *3GPP goes machine*: Machine-type communication received considerable attention in 3GPP. Back in the early 2010s, 3GPP focused considerable efforts on further development of Long-Term Evolution (LTE) radio by outlining the technology named LTE-MTC or LTE-M. Addressing the need for reduced cost and energy consumption while increasing the coverage range and the number of served devices per cell, the said technology has made so far several decisive steps, while being followed by the recently standardized narrowband IoT (NB-IoT) solution.

In September 2015, following the recent activities on cellular IoT condensed in TR 45.820 document, the work on NB-IoT has officially commenced. The new Cat. NB1 devices can be integrated into today's communication networks and enable UEs with about 10% complexity of that for Cat. 1. To achieve this goal, the bandwidth is reduced down to 180 kHz, orthogonal frequency-division multiple access (OFDMA) with 15 kHz subcarrier spacing for the downlink, frequency-division multiple access (FDMA) with 15 kHz subcarrier spacing and single-carrier FDMA with either 3.75 or 15 kHz between the subcarriers in the uplink. NB-IoT can offer three deployment options: standalone, in-band on the LTE carrier, or in the LTE guard band. The standardization process behind NB-IoT was completed in June 2016 and the solution was included into LTE Release 13. Presently, NB-IoT and LTE-M technologies are in active commercial deployment in Americas, Europe, Asia, and Australia.

IV. DEVELOPED EVALUATION METHODOLOGY

With the aim to characterize the tentative performance gains of various user involvement mechanisms, we concentrate on a




Fig. 3. Part of our representative urban IoT scenario: 300 m \times 300 m out of 1 km \times 1 km area is displayed.

representative urban use case that may correspond to several practical IoT applications (see Fig. 1): smart commuting, context-aware alerts, personalized advertisements, etc. The following text summarizes the considered deployment and network topology, the proposed user involvement strategies, and the details of our conducted simulation study.

1) *Deployment parameters:* In this work, we focus on a typical urban scenario over a 1 km² Manhattan grid deployment (see Fig. 3). A total of 100 city blocks are modeled. We consider two types of connected machines: stationary devices that represent smart road signs, environmental sensors, etc., and mobile wearable machines that offer healthcare, fitness, and well-being functionality. Following Google StreetView data on the density of road signs and pedestrians on a weekly basis in Manhattan, New York City, USA, the number of connected machines is set to its minimum feasible value of 20 pre-deployed devices per block and 30 wearable devices per block. This leads to 2,000 stationary and 3,000 moving machines across the entire simulation scenario. All of the modeled devices are deployed uniformly over the sidewalks.

We also model vehicles that participate in intense downtown traffic, where cars are driving along the streets with the constant speed of 30 km/h. The random inter-vehicle distance follows an exponential distribution with the mean of 3 m. At the intersections, we adopt the Manhattan mobility pattern: vehicles continue in the same direction with the probability of 0.5, while the chances to make a left or right turn are equal to 0.25. Pedestrians carrying wearable machines follow a similar mobility pattern with the speed of 5 km/h. To eliminate border effects and maintain uniform density of mobile objects (namely, moving machines and assisting vehicles), a wraparound mechanism is implemented, such that any mobile device leaving the area of interest on a side immediately appears on the opposite side of the map.

2) *Simulation details:* The reported performance assessment has been conducted with our custom-made system-level simulator, named WINTERSim, which has been extensively utilized recently for studying various IoT scenarios [12]. In the present study, we focus primarily on the uplink IoT traffic by modeling connectivity between a number of machines and the base station (BS). To fairly compare the behavior of all the

TABLE I
SIMULATION SETUP AND PARAMETERS

Parameter	Value
Message payload (stationary machine)	10 B
Message payload (moving machine)	100 B
Inter-arrival time (stationary machine)	5 s
Inter-arrival time (moving machine)	60 s
City block size	80 m
Street width	25 m
Scenario size (100 blocks)	1050 m \times 1050 m
Total number of stationary machines	2,000 / scenario
Total number of moving machines	3,000 / scenario
Base station height	10 m
Car roof height	1.5 m
Deployment height of stationary machines	Uniform in [0; 10) m
Deployment height of moving machines	1.5 m
Number of vehicles	1,000 / scenario
Number of pedestrians	3,000 / scenario
Speed of vehicles	30 km/h
Speed of pedestrians	5 km/h
Average inter-vehicle distance	3 m
Inter-vehicle distance distribution	Exponential
Mobility pattern of vehicles and pedestrians	"Manhattan"
Association rule	Max received power

four considered RATs (i.e., to avoid overloading SIGFOX), the data transmissions are assumed to be regular and infrequent. More specifically, stationary machines communicate 10 B messages every 5 s, while moving devices send a 100 B update every minute, which corresponds to the typical sensing-based applications (e.g., assessing user's physical condition with a medical sensor).

From the connectivity perspective, machines communicate with their serving BS by default (termed *baseline* connectivity). Alternatively, if a better signal level is available, the devices may also connect to one of the femtocell relay stations deployed on the mobile vehicles across the tracking area (termed *assisted* connectivity). To characterize the effects of involving user-owned relaying cars for the "average" IoT device, "median-quality" connections to the BS are of particular interest. Therefore, in our scenario the BS is located at a certain distance from the center of the area to ensure the baseline average signal-to-interference-plus-noise ratio (SINR) of 10 dB. Since the properties of the considered LPWAN RATs vary significantly, four different simulation setups have been considered (one per RAT), with the distances to the BS ranging from 520 m for Wi-Fi HaLow to 12 km for LoRaWAN. For the sake of better accuracy, the numerical results in each of these evaluations have been averaged over 100 independent simulation rounds.

Certain additional assumptions have been made to implement the LPWAN technologies of interest. Particularly, the hard message limitation for SIGFOX was relaxed. Then, LoRaWAN was restricted to operate exclusively over the 868 MHz band. The bandwidth of Wi-Fi HaLow, in its turn, was set to 1 MHz by disregarding the 2 MHz and wider bandwidth options that offer higher data rates for the cost of reduced coverage. Finally, only seven key MCSs were supported for NB-IoT. The remaining radio technology related parameters were adopted from Fig. 2, while other important settings are summarized in Table I.

In our subsequent evaluation, we focus on the two key metrics: (i) SINR at the receiver and (ii) energy efficiency of machines, which is defined as the amount of data that has been




Fig. 4. Average SINR values with various user involvement types.

reliably delivered from the IoT device to the BS in relation to the total energy consumed by the machine's radio interface.

3) *Degrees of user involvement*: As relaying vehicles in our IoT scenario are not owned by the operator but by the private users, the assisted connectivity option requires certain levels of user involvement. In this article, we study two different types of such engagement in the characteristic urban IoT deployment:

- *User involvement Type 1*. In this case, some of the driving vehicles share their communication capabilities and, in close proximity, can opportunistically forward the IoT traffic from the machines to the application server. The deployed machines compare the connection quality to the BS with that to the nearest vehicle that is willing to assist, and transmit their subsequent update over a better channel. In particular, the signal strength of the received beacon has been considered here as the selection criterion. In its turn, the assisting vehicle relays thus received IoT data to the application server over its on-board communication equipment.

- *User involvement Type 2*. As the user involvement Type 1 does not affect the vehicle mobility patterns, it can only offer opportunistic gains. On the contrary, the user involvement Type 2 suggests the car owner to temporarily park the vehicle close to the cluster of machines suffering from inadequate connection quality. For instance, the car owner may be offered as a reward a discounted parking permit in the said location (or free charging time in case of an electric vehicle). In this case, conforming vehicles are placed next to the centers of device clusters and start continuously forwarding the IoT data from the machines to the application server. Accordingly, a link with a better quality can be made available to the machines for longer intervals of time. However, the user involvement Type 2 may require humans to deviate from their intended mobility patterns and the corresponding sources of motivation should thus be provided.

The achievable performance gains in terms of machine's energy efficiency for both types of user involvement are reported in subsection V-A, while a discussion on the nature and the origins of user involvement is offered in subsection V-B.

V. BENEFITS AND NATURE OF USER INVOLVEMENT

A. Achievable Performance Gains

To ease further exposition, we only account for the proportion of data transmitted by the machines. To this aim, we reasonably assume that the wireless connections from the privately-owned vehicles (which are neither battery- nor

power-constrained) to the BS are reliable enough to guarantee the delivery of the relayed IoT data.

First, Fig. 4 reports on the average levels of SINR at the receiver (either the BS or the assisting vehicle, depending on the machine's current connectivity option). We learn that for all the IoT technologies in question the considered user involvement options notably outperform the baseline alternative. In particular, noticeable SINR gains are achieved already with a few assisting vehicles. The SINR gains for the SIGFOX solution are the highest, while the other three LPWAN protocols behave similarly as the degree of human assistance increases. The explanation behind these results is in the fact that SIGFOX operates in a full-power regime with a single data rate, while other RATs allow the machines to dynamically select their transmit power and MCS. The results for the user involvement Type 2 are, on average, several dB higher than the corresponding numbers for the user involvement Type 1, which confirms that careful positioning of assisting nodes is preferred over their opportunistic placement.

Further, Fig. 5 illustrates the impact of the studied user involvement types on the average energy efficiency of the communicating machines. This parameter offers insights into how far the battery life could be extended and, consequently, how much the operating costs could be reduced. In the figure, we first observe a marginal impact of user involvement on the energy efficiency of SIGFOX. Albeit substantial improvements in the SINR values are confirmed by Fig. 4, the single transmit power level in SIGFOX limits the potential benefits of the assisting vehicles. The observed gain of only several percent is due to a slightly increased level of reliability.

On the contrary, the alternative three RATs demonstrate considerable energy efficiency improvements (e.g., up to 4 times higher energy efficiency for NB-IoT with user involvement Type 2). The observed growth is not only due to better channel conditions (which are similar for the said technologies in the same scenario), but also due to the flexibility of the IoT RATs themselves (specifically, more freedom in the MCS and transmit power selection). *In summary, the considered ways of user involvement may lead to notable improvements in the IoT service reliability (due to higher SINR) as well as in the energy efficiency of networked machines. Hence, people in the loop assist the operator in reducing both the capital investments and the operating costs. We now discuss several approaches to materializing these tentative gains.*




Fig. 5. Energy-efficiency (EE) gains with various user involvement types.

B. User Incentivization Options

A crucial component of the considered system operation is conditional on user's willingness to share own resources while helping improve the IoT network performance. Even though the concept of user involvement for resource provisioning has been discussed for years in the context of various mobile systems, these mechanisms have not been implemented widely as of yet. This is in part owing to conservative human nature that resists new models of service provisioning, especially when the process requires involving own resources without immediately perceived benefits.

We expect that appropriate user incentivization mechanisms need to be natively integrated into the envisioned IoT infrastructure. In systems with regular topologies and central control – that emerge primarily in the industrial context – there always remains an opportunity to enable resource sharing by design. On the contrary, strictly enforcing resource sharing in consumer scenarios may lead to customer dissatisfaction and therefore clever incentivization mechanisms are required.

To develop appropriate incentivization schemes for the consumer context, one has to mediate between dissimilar interests of at least five major stakeholders: (i) owners of the pre-deployed machines; (ii) owners of the wearable machines; (iii) owners of the assisting vehicles; (iv) car manufacturers, and (v) system operators. Furthermore, in order to deploy the discussed mechanisms in practice, the operators need to carefully “moderate the dialog” between all of these parties, where the most non-trivial aspect is to engage the owners of vehicles.

In order to make it happen, a service provider has to offer (i) a type of compensation for the car owners and (ii) a corresponding billing mechanism. For the former, there is a set of options including those directly related to the operator–user relationships, such as decreased monthly rates and/or extended subscription periods, as well as priority in service, guaranteed rate during congestion, etc.

Further, a billing mechanism is a necessary component of the incentive-driven services. The set of requirements imposed on its choice includes robustness to a loss of control connection, high levels of security during authorization and encryption of all the exchanged billing-specific information, operational accuracy, as well as simplicity. There are two fundamental paths to implementing an efficient billing algorithm.

In a fully centralized system, the operators become responsible for all the phases, such as collection, storage, and

interpretation of information on the individual contributions by the users. To alleviate the cases of false notification by malicious participants, each session has to be authorized and data needs to be collected from both endpoints. In case of a multi-tenant deployment, a dedicated entity needs to be empowered to account, store, and distribute the rewards collected by the stakeholders [13].

An alternative to the above is a network-assisted decentralized billing solution [14]. There are numerous practical contexts, where decentralized incentivization mechanisms have been deployed successfully. A famous example is peer-to-peer file sharing and streaming services. There, reciprocity-based mechanisms where the peers maintain and share the information about other peers' contributions remain a popular method. In such schemes, network assistance is still required for authentication purposes, but the actual billing process could be made decentralized.

VI. CONCLUSIONS

The unprecedented proliferation of the interconnected autonomous machines drastically increases the intensity and the depth of human–machine interactions. On the one hand, this introduces a wide range of novel challenges with respect to how the individual procedures, technologies, as well as the overall working services and applications should be engineered – mindful of the unique capabilities and limitations of humans and machines alike. On the other hand, this brings along an excellent opportunity to jointly engage both sides to take advantage of rich mutual collaboration and shield any weaknesses with each other's strengths. In this article, we have confirmed that this remains valid for people as well as for connected machines.

Our novel analysis of an illustrative consumer IoT scenario for different user involvement levels and over four perspective radio technologies demonstrates that even moderate human assistance makes a decisive difference and unlocks significant energy savings for networked machines. Importantly, our offered numerical results suggest that while each of the addressed wireless solutions does benefit from keeping people in the loop, the actual gains for every system profile depend on the flexibility of the underlying access protocol. At the same time, the costs associated with involving the human context may include certain incentivization-related expenditures. These may vary a lot in the envisaged heterogeneous, multi-tenant deployments, which calls for careful planning of

1 user engagement in future people-centric IoT infrastructure.
 2 Ultimately, the rapidly maturing human-aware IoT ecosystem
 3 may become a new global utility, thus “disappearing” in the
 4 “fabric of everyday life” [15], while enabling a plethora of
 5 next-generation applications and services.
 6

7 ACKNOWLEDGMENT

8 The authors are particularly grateful to Yngve Selén (Wire-
 9 less Access Networks Department, Ericsson Research) for the
 10 insightful comments that allowed to improve this paper.
 11

12 REFERENCES

- 13 [1] D. Nunes et al., “Human-in-the-loop Connectivity Management in
 14 Smartphones,” Proc. 14th Int. Conf. Wired/Wireless Internet Commun.,
 15 May 2016, pp. 159-170.
- 16 [2] Y. Mehmood et al., “Internet-of-Things-Based Smart Cities: Recent
 17 Advances and Challenges,” IEEE Commun. Mag., vol. 55, no. 9, Sept.
 18 2017, pp. 16-24.
- 19 [3] E. Ahmed et al., “Internet-of-Things-based Smart Environments: State
 20 of the Art, Taxonomy, and Open Research Challenges,” IEEE Wireless
 21 Commun., vol. 23, no. 5, Oct. 2016, pp. 10-16.
- 22 [4] D. S. Nunes, P. Zhang, and J. S. Silva, “A Survey on Human-in-the-Loop
 23 Applications Towards an Internet of All,” IEEE Commun. Surveys &
 24 Tutorials, vol. 17, no. 2, 2015, pp. 944-965.
- 25 [5] L. Duan et al., “Human-in-the-Loop Mobile Networks: A Survey of
 26 Recent Advancements,” IEEE J. on Sel. Areas in Commun., vol. 35, no.
 27 4, Apr. 2017, pp. 813-831.
- 28 [6] L. Yang et al., “People-Centric Cognitive Internet of Things for the
 29 Quantitative Analysis of Environmental Exposure,” IEEE Internet of
 30 Things J., vol. 5, no. 4, Aug. 2018, pp. 2353-2366.
- 31 [7] R. Schoenen, H. Yanikomeroglu, and B. Walke, “User in the Loop:
 32 Mobility Aware Users Substantially Boost Spectral Efficiency of Cellular
 33 OFDMA Systems,” IEEE Commun. Letters, vol. 15, no. 5, May 2011,
 34 pp. 488-490.
- 35 [8] B. Guo et al., “Mobile Crowd Sensing and Computing: The Review
 36 of an Emerging Human-Powered Sensing Paradigm,” ACM Computing
 37 Surveys, vol. 48, no. 1, Aug. 2015, pp. 1-31.
- 38 [9] J. A. Stankovic, “Research Directions for the Internet of Things,” IEEE
 39 Internet of Things J., vol. 1, no. 1, Feb. 2014, pp. 3-9.
- 40 [10] S. Feng, P. Setoodeh, and S. Haykin, “Smart Home: Cognitive Interactive
 41 People-Centric Internet of Things,” IEEE Commun. Mag., vol. 55, no.
 42 2, Feb. 2017, pp. 34-39.
- 43 [11] F. Adeltado et al., “Understanding the Limits of LoRaWAN,” IEEE
 44 Commun. Mag., vol. 55, no. 9, Sept. 2017, pp. 34-40.
- 45 [12] S. Andreev et al., “Understanding the IoT Connectivity Landscape:
 46 A Contemporary M2M Radio Technology Roadmap,” IEEE Commun.
 47 Mag., vol. 53, no. 9, Sept. 2015, pp. 32-40.
- 48 [13] A. Yousafzai et al., “Directory-Based Incentive Management Services
 49 for Ad-Hoc Mobile Clouds,” Int’l J. Info. Management, vol. 36, no. 6,
 50 Dec. 2016, pp. 900-906.
- 51 [14] R. Schoenen, H. U. Sokun, and H. Yanikomeroglu, “Green Cellular
 52 Demand Control with User-in-the-Loop Enabled by Smart Data Pricing
 53 Using an Effective Quantum (eBit) Tariff,” Proc. IEEE VTC-Fall, Sept.
 54 2016, pp. 1-7.
- 55 [15] M. S. Corson et al., “Toward Proximity-aware Internetworking,” IEEE
 56 Wireless Commun., vol. 17, no. 6, Dec. 2010, pp. 26-33.

57 AUTHORS’ BIOGRAPHIES

58 **Vitaly Petrov** (vitaly.petrov@tut.fi) is a PhD candidate at
 59 the Laboratory of Electronics and Communications Engineer-
 60 ing at Tampere University of Technology (TUT), Finland. He
 received the Specialist degree (2011) from SUAI University,
 St. Petersburg, Russia, as well as the M.Sc. degree (2014)
 from TUT. He was a Visiting Scholar with Georgia Institute of
 Technology, Atlanta, USA, in 2014. Vitaly (co-)authored more
 than 30 published research works on terahertz band commu-
 nications, Internet-of-Things, nanonetworks, cryptology, and
 network security.

Konstantin Mikhaylov (konstantin.mikhaylov@oulu.fi) re-
 ceived his B.Sc. (2006) and M.Sc. (2008) degrees in elec-
 trical engineering, with a focus on wireless systems, from
 St. Petersburg State Polytechnical University, St. Petersburg,
 Russia. Since 2009, he has been a researcher for wireless and
 embedded systems at the University of Oulu, Finland. His
 research interests include resource-constrained embedded sys-
 tems, energy-efficient wireless communication technologies,
 wireless sensor and actuator networks.

Dmitri Moltchanov (dmitri.moltchanov@tut.fi) is a senior
 research scientist at Tampere University of Technology (TUT).
 He received his M.Sc. and Cand.Sc. degrees from Saint Pe-
 tersburg State University of Telecommunications in 2000 and
 2002, respectively, and his Ph.D. degree from TUT in 2006.
 His research interests include performance evaluation and
 optimization issues in IP networks, Internet traffic dynamics,
 and traffic localization in P2P networks.

Sergey Andreev (sergey.andreev@tut.fi) is a Senior Re-
 search Scientist in the Laboratory of Electronics and Commu-
 nications Engineering at Tampere University of Technology,
 Finland. He received the Specialist degree (2006) and the
 Cand.Sc. degree (2009) both from St. Petersburg State Uni-
 versity of Aerospace Instrumentation, St. Petersburg, Russia,
 as well as the Ph.D. degree (2012) from Tampere University
 of Technology. Sergey (co-)authored more than 100 published
 research works on wireless communications, energy efficiency,
 and heterogeneous networking.

Gabor Fodor (gabor.fodor@ericsson.com) received his
 Ph.D. degree in teletraffic theory from Budapest University
 of Technology and Economics, Hungary, in 1998. Since then,
 he has been with Ericsson Research, Stockholm, Sweden.
 He is currently a master researcher with specialization in
 modeling, performance analysis, and protocol development for
 wireless access networks. He has authored around 50 papers
 in reviewed conference proceedings and journals, and holds
 over 40 patents (granted or pending).

Johan Torsner (johan.torsner@ericsson.com) is a research
 manager in Ericsson Research and is currently leading Eric-
 csson’s research activities in Finland. He joined Ericsson
 in 1998, and has held several positions within research and
 R&D. He has been deeply involved in the development and
 standardization of 3G and 4G systems, and has led over 100
 patent applications. His current research interests include 4G
 evolution, 5G, and machine-type communication.

Halim Yanikomeroglu (halim@sce.carleton.ca) is a full
 professor in the Department of Systems and Computer En-
 gineering at Carleton University. His research interests cover
 many aspects of wireless technologies with special emphasis
 on cellular networks. His collaborative research with industry
 has resulted in about 25 patents (granted and applied). He
 is a Distinguished Lecturer for the IEEE Communications
 Society and a Distinguished Speaker for the IEEE Vehicular
 Technology Society.

Markku Juntti (markku.juntti@oulu.fi) received a Dr.Sc.
 (Tech.) degree in electrical engineering from the University
 of Oulu, Finland, in 1997. He has been with the University of
 Oulu since 1992. In 1994–1995 he visited Rice University,

1
2 Houston, Texas. He has been a professor of telecommuni-
3 cations at the University of Oulu since 2000. His research
4 interests include communication and information theory, signal
5 processing for wireless communication systems, and their
6 application in wireless communication system design.

7 **Yevgeni Koucheryavy** (evgeni.koucheryavy@tut.fi) is a Full
8 Professor at the Laboratory of Electronics and Communi-
9

10
11 cations Engineering of Tampere University of Technology
12 (TUT), Finland. He received his Ph.D. degree (2004) from
13 TUT. He is the author of numerous publications in the field of
14 advanced wired and wireless networking and communications.
15 He is Associate Technical Editor of IEEE Communications
16 Magazine and Editor of IEEE Communications Surveys and
17 Tutorials.
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

For Review Only

I. Introduction and Vision

The Internet of Things (IoT) has undergone a fundamental transformation in recent decades: departing from the legacy radio frequency identification (RFID) technology of the 1980s and the wireless sensor networks of the 1990s, which were essentially siloed "connectivity islands" with limited interoperability, to its present form, which is becoming increasingly interconnected and heterogeneous. Today's IoT is already a fusion of numerous networked tools and appliances, equipped with advanced computational intelligence and rich communication capabilities. More broadly, the principles of contemporary IoT overlap with and permeate many adjacent domains, including mobile and pervasive computing, as well as robotics and cyber-physical systems -- with applications ranging from smartphone-based social networking that reduces traffic and pollution in cities to mission-critical industrial automation that monitors and actuates over factory processes [1].

Beyond legacy embedded systems with constrained applicability, the emerging IoT solutions are becoming more open and integrated by adaptively combining sensors and actuators with actionable intelligence for automatic monitoring and control [2]. However, as a multitude of interconnected and intelligent machines communicate with each other and autonomously adapt to changing contexts without user involvement, the fact that present technology is made by humans and for humans is often overlooked [3]. Indeed, modern IoT systems are still widely unaware of the human context and instead consider people to be an external and unpredictable element in their control loop. Therefore, future IoT applications will need to intimately involve humans, so that people and machines could operate synergistically. To this end, human intentions, actions, psychological and physiological states, and even emotions could be detected, inferred through sensory data, and utilized as control feedback.

This concept, which is known as human-in-the-loop (HITL), becomes a logical next step toward truly social computing and communication in smart cities [4]. HITL opens the door to next-generation people-oriented IoT platforms, which are aware of the people context, mobility, and even mood, thus having more efficient and intuitive manipulation [5]. As users increasingly interact with such human-aware HITL systems, they may also become directly influenced by the control-loop decisions, thereby closing the loop [6]. In fact, people may receive control input from the system in the form of suggestions and incentives (or even penalties) to diverge from their default behavior. Accordingly, human behavior may be impacted in either space (for example, the users are encouraged to move to a less congested location) or time (for example, the users are convinced to reduce their current data demand in case the network is overloaded); this is known as the "user-in-the-loop" (UIL) [7].

With UIL, often referred to as "layer 8", the space-time user traffic demand may be shaped opportunistically and better matched with the actual resource supply from the people-centric wireless system. While HITL involves the user whenever

1
2
3 human participation is desired or required and UIL extends the user's role
4 beyond a traffic-generating and traffic-consuming black box, these trends must
5 account for the fact that people are, in essence, walking sensor networks [8].
6 Indeed, a wide diversity of user-owned companion devices, such as mobile
7 phones, wearables, connected vehicles, and even drones may become an integral
8 part of the IoT infrastructure. Hence, they can augment a broad range of
9 applications, in which human context is useful, including traffic planning,
10 environmental monitoring, mobile social recommendation, and public safety,
11 among others. Therefore, we envision that -- in contrast to past concepts where
12 the user only assists the network to receive better individual service -- future
13 user equipment will truly merge with the IoT architecture to form a deep-fused
14 human--machine system that efficiently utilizes the complementary nature of
15 human and machine intelligence.
16
17

18 Should the IoT keep people in the loop, it has the potential to evolve into an
19 integrated multi-tenant system-of-systems that may form novel, unprecedented
20 services [9]. For instance, the underlying people-centric sensor and actuator
21 network may act as a utility – similar to electricity and water – creating
22 important usable knowledge from vast amounts of data. Facilitated by this new
23 global utility, different IoT devices and networks that previously had nothing to
24 do with each other may discover and start talking to one another, thereby
25 augmenting the current talk-by-design approaches. While the existing studies
26 primarily focus on how the IoT can serve humans in various scenarios [2][10] in
27 this work we maintain that people can also assist the IoT in its daily tasks, thus
28 closing the loop. This proposed vision renders the next-generation IoT as a
29 genuinely multi-user, multi-tenant, and multi-application platform that can be
30 materialized in the near future by relying on the emerging IoT radio
31 technologies.
32
33

34
35 Following our offered vision, this article reviews and classifies the people-centric
36 applications related to the long-range radio solutions. We then describe and
37 compare the prominent IoT-enabling radio access technologies (RATs), namely,
38 SIGFOX, LoRaWAN, Wi-Fi HaLow, and NarrowBand IoT. Further, we present a
39 case study for the people-centric IoT system, which investigates how the listed
40 RATs respond to the representative human involvement models and quantify the
41 resultant system-wide benefits. We finally discuss attractive incentivization
42 mechanisms for the IoT to keep its users in the loop, thus aiming for a synergy
43 between the human-centric and the IoT-centric segments of the future Internet.
44
45

46 47 **II. Envisaged People-Centric IoT Applications**

48

49 In light of the above, a contemporary perspective on the IoT expects it to soon
50 become “the infrastructure of the information society”. The very capable
51 machines, ranging from sensors to vehicles, are already assisting humans in their
52 daily lives. Explosive growth in the population of such connected objects leads to
53 complex human-machine interactions that become increasingly frequent,
54 facilitated by the HITL and UIL concepts. As these interactions intensify, many
55
56
57
58
59
60

categories of people-centric IoT services emerge and are expected to be deployed over the following years:

- *Intention- and mission-aware services.* These services primarily reflect user's current intention or desire and assist by enabling, for example, situation-aware smart commuting for pedestrians, cyclists, and drivers of scooters, trucks, and other vehicles. This group of applications can help people in a variety of use cases, from highlighting the nearest available parking space on a vehicle's head-up display in urban areas to status reporting on a display or augmented reality (AR) glasses in challenging environments, such as mines, construction sites, etc.
- *Location- and context-aware services.* Another group of services is formed by location- and context-aware applications, such as those communicating alerts from environmental sensors (for example, "put on/take off your mask" when entering/leaving a polluted area). Many more of these services are envisioned to be deployed in the coming years, such as identifying slippery floors and low ceilings, notifying about forgotten trash when a user is about to leave the house, and many other examples.
- *Condition- and mood-aware services.* A deeper level of IoT penetration into people's lives can be achieved by integrating city/area infrastructure with personal medical and wellness devices. For instance, dietary restrictions could be applied on a menu when ordering food or a squad leader may be advised to give a break to a worker whose blood pressure has recently gone up.

Summarizing the above examples of services, we note that depending on the environment the set of requirements and challenges to implement a particular application may vary considerably. To further offer a challenges-based grouping, we propose to differentiate between two major contexts: consumer and industrial (see Fig. 1). The former is characterized by the presence of numerous devices that are heterogeneous in terms of their communication means and ownership. Therefore, the major challenge in this context is to provide sufficient *scalability* of the deployed connectivity solution. On the contrary, the latter context is more challenging in terms of maintaining communication *reliability* due to more difficult propagation environments. At the same time, the system operator has more control over device population in such areas.

We continue by addressing how people-centric IoT applications are to be engineered, that is, which radio technologies need to be employed in particular scenarios and how to ensure their suitability for the target operating conditions.

III. Review of Wireless Connectivity Options

Inspired by the above use cases, we review the contemporary IoT radio access technologies and analyze them through the prism of their applicability for HITL

1
2
3 applications. Fig. 2 brings together the major characteristics of the considered
4 RATs.
5

6 *1) Current technology diversity:* The demand for developing RATs that focus
7 specifically on the needs of machines was commonly understood in the mid to
8 late 2000s. The low power consumption, affordable cost, high communication
9 range, and capability to handle massive deployments of infrequently
10 transmitting devices became the major requirements for these new solutions,
11 which can be collectively referred to as Low-Power Wide-Area Networks
12 (LPWANs). Development of such technologies progressed in parallel within
13 leading standardization bodies, including IEEE, ETSI, and 3GPP.
14
15

16 This resulted in the sheer diversity of today's LPWAN options, which comprise a
17 number of standardized solutions. Across this diversity, the paths taken by the
18 technology developers differ substantially. To offer illustrative examples, we
19 consider two emerging LPWAN solutions, namely, SIGFOX and LoRaWAN [11].
20 Both technologies operate in the sub-GHz license-exempt industrial, scientific,
21 and medical (ISM) frequency bands and employ ALOHA-based channel access
22 with frequency hopping, which places them under severe duty cycle restrictions.
23 Topologically, both alternatives adhere to a cellular-like structure.
24
25

26 The SIGFOX solution operates with ultra-narrow band signals: 100 Hz using
27 Binary Phase-Shift Keying modulation and 600 Hz using Gaussian Frequency
28 Shift Keying modulation for uplink and downlink, respectively. Some limitations
29 of this technology are harsh restrictions on the application payload of a radio
30 frame (i.e., 12 bytes at most), the single modulation and coding scheme (MCS),
31 and the limitation on the number of packets that can be sent to and from a device
32 per day to 4 and 140, respectively. Today's SIGFOX installation base exceeds 2.5
33 million devices.
34
35

36 In contrast to SIGFOX, LoRaWAN supports multiple MCSs. The mandatory MCSs
37 are based on the Semtech's proprietary LoRa spread spectrum modulation
38 derived from the chirp spread spectrum modulation. The number of chirps to
39 carry a single bit as well as the bandwidth of the channel that affects the duration
40 of a single chirp can be adjusted to trade the on-air time for the transmission
41 range. There are currently several commercial deployments of LoRaWAN with
42 the overall number of chips in excess of 5 million.
43
44

45 *2) Machines talk Wi-Fi:* The path followed by the IEEE 802.11 community is
46 substantially different. The work on IEEE 802.11ah standard (also known as Wi-
47 Fi HaLow) has approached its final stage and early chipsets implementing this
48 technology are already announced. The solution targets the "high-end" devices
49 with demanding performance requirements in terms of throughput and latency.
50 To this end, 802.11ah delivers a non-backward compatible communication
51 technology in the sub-1 GHz ISM band, which is based on orthogonal frequency
52 division multiplexing (OFDM) and features several dozens of different channel
53 bandwidths as well as modulation and coding options. Wi-Fi HaLow does not
54 have any large commercial installations yet, as the technology has recently
55 entered the testing phase.
56
57
58
59
60

1
2
3
4 One of the intrigues that remain today is how close the relationship between the
5 HaLow and the conventional Wi-Fi systems will be. That is, whether HaLow
6 continues on its own or be merged with the traditional Wi-Fi to form dual-mode
7 devices similar to Bluetooth Smart: for example, dual technology enabled access
8 points or Wi-Fi HaLow access points combined with a Wi-Fi client to be used in a
9 smartphone.

10
11
12 *3) 3GPP goes machine:* Machine-type communication received considerable
13 attention in 3GPP. Back in the early 2010s, 3GPP focused considerable efforts on
14 further development of Long-Term Evolution (LTE) radio by outlining the
15 technology named LTE-MTC or LTE-M. Addressing the need for reduced cost and
16 energy consumption while increasing the coverage range and the number of
17 served devices per cell, the said technology has made so far several decisive
18 steps, while being followed by the recently standardized narrowband IoT (NB-
19 IoT) solution.

20
21
22 In September 2015, following the recent activities on cellular IoT condensed in
23 TR 45.820 document, the work on NB-IoT has officially commenced. The new
24 Cat. NB1 devices can be integrated into today's communication networks and
25 enable UEs with about 10% complexity of that for Cat. 1. To achieve this goal, the
26 bandwidth is reduced down to 180 kHz, orthogonal frequency-division multiple
27 access (OFDMA) with 15 kHz subcarrier spacing for the downlink, frequency-
28 division multiple access (FDMA) with 15 kHz subcarrier spacing and single-
29 carrier FDMA with either 3.75 or 15 kHz between the subcarriers in the uplink.
30 NB-IoT can offer three deployment options: standalone, in-band on the LTE
31 carrier, or in the LTE guard band. The standardization process behind NB-IoT
32 was completed in June 2016 and the solution was included into LTE Release 13.
33 Presently, NB-IoT and LTE-M technologies are in active commercial deployment
34 in Americas, Europe, Asia, and Australia.

35 36 37 38 **IV. Developed Evaluation Methodology**

39
40
41 With the aim to characterize the tentative performance gains of various user
42 involvement mechanisms, we concentrate on a representative urban use case
43 that may correspond to several practical IoT applications (see Fig. 1): smart
44 commuting, context-aware alerts, personalized advertisements, etc. The
45 following text summarizes the considered deployment and network topology,
46 the proposed user involvement strategies, and the details of our conducted
47 simulation study.

48
49
50 *1) Deployment parameters:* In this work, we focus on a typical urban scenario
51 over a 1 km² Manhattan grid deployment (see Fig. 3). A total of 100 city blocks
52 are modeled. We consider two types of connected machines: stationary devices
53 that represent smart road signs, environmental sensors, etc., and mobile
54 wearable machines that offer healthcare, fitness, and well-being functionality.
55 Following Google StreetView data on the density of road signs and pedestrians
56 on a weekly basis in Manhattan, New York City, USA, the number of connected
57
58
59
60

1
2
3 machines is set to its minimum feasible value of 20 pre-deployed devices per
4 block and 30 wearable devices per block. This leads to 2,000 stationary and
5 3,000 moving machines across the entire simulation scenario. All of the modeled
6 devices are deployed uniformly over the sidewalks.
7

8 We also model vehicles that participate in intense downtown traffic, where cars
9 are driving along the streets with the constant speed of 30 km/h. The random
10 inter-vehicle distance follows an exponential distribution with the mean of 3 m.
11 At the intersections, we adopt the Manhattan mobility pattern: vehicles continue
12 in the same direction with the probability of 0.5, while the chances to make a left
13 or right turn are equal to 0.25. Pedestrians carrying wearable machines follow a
14 similar mobility pattern with the speed of 5 km/h. To eliminate border effects
15 and maintain uniform density of mobile objects (namely, moving machines and
16 assisting vehicles), a wraparound mechanism is implemented, such that any
17 mobile device leaving the area of interest on a side immediately appears on the
18 opposite side of the map.
19
20

21
22 *2) Simulation details:* The reported performance assessment has been conducted
23 with our custom-made system-level simulator, named WINTERSim, which has
24 been extensively utilized recently for studying various IoT scenarios [12]. In the
25 present study, we focus primarily on the uplink IoT traffic by modeling
26 connectivity between a number of machines and the base station (BS). To fairly
27 compare the behavior of all the four considered RATs (i.e., to avoid overloading
28 SIGFOX), the data transmissions are assumed to be regular and infrequent. More
29 specifically, stationary machines communicate 10 B messages every 5 s, while
30 moving devices send a 100 B update every minute, which corresponds to the
31 typical sensing-based applications (e.g., assessing user's physical condition with
32 a medical sensor).
33

34
35 From the connectivity perspective, machines communicate with their serving BS
36 by default (termed *baseline* connectivity). Alternatively, if a better signal level is
37 available, the devices may also connect to one of the femtocell relay stations
38 deployed on the mobile vehicles across the tracking area (termed *assisted*
39 connectivity). To characterize the effects of involving user-owned relaying cars
40 for the "average" IoT device, "median-quality" connections to the BS are of
41 particular interest. Therefore, in our scenario the BS is located at a certain
42 distance from the center of the area to ensure the baseline average signal-to-
43 interference-plus-noise ratio (SINR) of 10 dB. Since the properties of the
44 considered LPWAN RATs vary significantly, four different simulation setups have
45 been considered (one per RAT), with the distances to the BS ranging from 520 m
46 for Wi-Fi HaLow to 12 km for LoRaWAN. For the sake of better accuracy, the
47 numerical results in each of these evaluations have been averaged over 100
48 independent simulation rounds.
49
50

51
52 Certain additional assumptions have been made to implement the LPWAN
53 technologies of interest. Particularly, the hard message limitation for SIGFOX was
54 relaxed. Then, LoRaWAN was restricted to operate exclusively over the 868 MHz
55 band. The bandwidth of Wi-Fi HaLow, in its turn, was set to 1 MHz by
56 disregarding the 2 MHz and wider bandwidth options that offer higher data rates
57
58
59
60

1
2
3 for the cost of reduced coverage. Finally, only seven key MCSs were supported
4 for NB-IoT. The remaining radio technology related parameters were adopted
5 from Fig. 2, while other important settings are summarized in Table I.
6

7
8 In our subsequent evaluation, we focus on the two key metrics: (i) SINR at the
9 receiver and (ii) energy efficiency of machines, which is defined as the amount of
10 data that has been reliably delivered from the IoT device to the BS in relation to
11 the total energy consumed by the machine's radio interface.
12

13 *3) Degrees of user involvement:* As relaying vehicles in our IoT scenario are not
14 owned by the operator but by the private users, the assisted connectivity option
15 requires certain levels of user involvement. In this article, we study two different
16 types of such engagement in the characteristic urban IoT deployment:
17

- 18 • *User involvement Type 1.* In this case, some of the driving vehicles share
19 their communication capabilities and, if in close proximity, can
20 opportunistically forward the IoT traffic from the machines to the
21 application server. The deployed machines compare the connection
22 quality to the BS with that to the nearest vehicle that is willing to assist,
23 and transmit their subsequent update over a better channel. In particular,
24 the signal strength of the received beacon has been considered here as
25 the selection criterion. In its turn, the assisting vehicle relays thus
26 received IoT data to the application server over its on-board
27 communication equipment.
28
- 29 • *User involvement Type 2.* As the user involvement Type 1 does not affect
30 the vehicle mobility patterns, it can only offer opportunistic gains. On the
31 contrary, the user involvement Type 2 suggests the car owner to
32 temporarily park the vehicle close to the cluster of machines suffering
33 from inadequate connection quality. For instance, the car owner may be
34 offered as a reward a discounted parking permit in the said location (or
35 free charging time in case of an electric vehicle). In this case, conforming
36 vehicles are placed next to the centers of device clusters and start
37 continuously forwarding the IoT data from the machines to the
38 application server. Accordingly, a link with a better quality can be made
39 available to the machines for longer intervals of time. However, the user
40 involvement Type 2 may require humans to deviate from their intended
41 mobility patterns and the corresponding sources of motivation should
42 thus be provided.
43
44
45
46

47 The achievable performance gains in terms of machine's energy efficiency for
48 both types of user involvement are reported in subsection V-A, while a
49 discussion on the nature and the origins of user involvement is offered in
50 subsection V-B.
51

52 53 **V. Benefits and Nature of User Involvement** 54 55 56 57 58 59 60

A. Achievable Performance Gains

To ease further exposition, we only account for the proportion of data transmitted by the machines. To this aim, we reasonably assume that the wireless connections from the privately-owned vehicles (which are neither battery- nor power-constrained) to the BS are reliable enough to guarantee the delivery of the relayed IoT data.

First, Fig. 4 reports on the average levels of SINR at the receiver (either the BS or the assisting vehicle, depending on the machine's current connectivity option). We learn that for all the IoT technologies in question the considered user involvement options notably outperform the baseline alternative. In particular, noticeable SINR gains are achieved already with a few assisting vehicles. The SINR gains for the SIGFOX solution are the highest, while the other three LPWAN protocols behave similarly as the degree of human assistance increases. The explanation behind these results is in the fact that SIGFOX operates in a full-power regime with a single data rate, while other RATs allow the machines to dynamically select their transmit power and MCS. The results for the user involvement Type 2 are, on average, several dB higher than the corresponding numbers for the user involvement Type 1, which confirms that careful positioning of assisting nodes is preferred over their opportunistic placement.

Further, Fig. 5 illustrates the impact of the studied user involvement types on the average energy efficiency of the communicating machines. This parameter offers insights into how far the battery life could be extended and, consequently, how much the operating costs could be reduced. In the figure, we first observe a marginal impact of user involvement on the energy efficiency of SIGFOX. Albeit substantial improvements in the SINR values are confirmed by Fig. 4, the single transmit power level in SIGFOX limits the potential benefits of the assisting vehicles. The observed gain of only several percent is due to a slightly increased level of reliability.

On the contrary, the alternative three RATs demonstrate considerable energy efficiency improvements (e.g., up to 4 times higher energy efficiency for NB-IoT with user involvement Type 2). The observed growth is not only due to better channel conditions (which are similar for the said technologies in the same scenario), but also due to the flexibility of the IoT RATs themselves (specifically, more freedom in the MCS and transmit power selection). *In summary, the considered ways of user involvement may lead to notable improvements in the IoT service reliability (due to higher SINR) as well as in the energy efficiency of networked machines. Hence, people in the loop assist the operator in reducing both the capital investments and the operating costs.* We now discuss several approaches to materializing these tentative gains.

B. User Incentivization Options

A crucial component of the considered system operation is conditional on user's willingness to share own resources while helping improve the IoT network

1
2
3 performance. Even though the concept of user involvement for resource
4 provisioning has been discussed for years in the context of various mobile
5 systems, these mechanisms have not been implemented widely as of yet. This is
6 in part owing to conservative human nature that resists new models of service
7 provisioning, especially when the process requires involving own resources
8 without immediately perceived benefits.
9

10 We expect that appropriate user incentivization mechanisms need to be natively
11 integrated into the envisioned IoT infrastructure. In systems with regular
12 topologies and central control – that emerge primarily in the industrial context –
13 there always remains an opportunity to enable resource sharing by design. On
14 the contrary, strictly enforcing resource sharing in consumer scenarios may lead
15 to customer dissatisfaction and therefore clever incentivization mechanisms are
16 required.
17
18

19 To develop appropriate incentivization schemes for the consumer context, one
20 has to mediate between dissimilar interests of at least five major stakeholders:
21 (i) owners of the pre-deployed machines; (ii) owners of the wearable machines;
22 (iii) owners of the assisting vehicles; (iv) car manufacturers, and (v) system
23 operators. Furthermore, in order to deploy the discussed mechanisms in
24 practice, the operators need to carefully “moderate the dialog” between all of
25 these parties, where the most non-trivial aspect is to engage the owners of
26 vehicles.
27
28

29 In order to make it happen, a service provider has to offer (i) a type of
30 compensation for the car owners and (ii) a corresponding billing mechanism. For
31 the former, there is a set of options including those directly related to the
32 operator-user relationships, such as decreased monthly rates and/or extended
33 subscription periods, as well as priority in service, guaranteed rate during
34 congestion, etc.
35
36

37 Further, a billing mechanism is a necessary component of the incentive-driven
38 services. The set of requirements imposed on its choice includes robustness to a
39 loss of control connection, high levels of security during authorization and
40 encryption of all the exchanged billing-specific information, operational
41 accuracy, as well as simplicity. There are two fundamental paths to
42 implementing an efficient billing algorithm.
43
44

45 In a fully centralized system, the operators become responsible for all the
46 phases, such as collection, storage, and interpretation of information on the
47 individual contributions by the users. To alleviate the cases of false notification
48 by malicious participants, each session has to be authorized and data needs to be
49 collected from both endpoints. In case of a multi-tenant deployment, a dedicated
50 entity needs to be empowered to account, store, and distribute the rewards
51 collected by the stakeholders [13].
52

53 An alternative to the above is a network-assisted decentralized billing solution
54 [14]. There are numerous practical contexts, where decentralized incentivization
55 mechanisms have been deployed successfully. A famous example is peer-to-peer
56
57
58
59
60

1
2
3 file sharing and streaming services. There, reciprocity-based mechanisms where
4 the peers maintain and share the information about other peers' contributions
5 remain a popular method. In such schemes, network assistance is still required
6 for authentication purposes, but the actual billing process could be made
7 decentralized.
8
9

10 VI. Conclusions

11
12
13 The unprecedented proliferation of the interconnected autonomous machines
14 drastically increases the intensity and the depth of human--machine interactions.
15 On the one hand, this introduces a wide range of novel challenges with respect to
16 how the individual procedures, technologies, as well as the overall working
17 services and applications should be engineered – mindful of the unique
18 capabilities and limitations of humans and machines alike. On the other hand,
19 this brings along an excellent opportunity to jointly engage both sides to take
20 advantage of rich mutual collaboration and shield any weaknesses with each
21 other's strengths. In this article, we have confirmed that this remains valid for
22 people as well as for connected machines.
23

24
25 Our novel analysis of an illustrative consumer IoT scenario for different user
26 involvement levels and over four perspective radio technologies demonstrates
27 that even moderate human assistance makes a decisive difference and unlocks
28 significant energy savings for networked machines. Importantly, our offered
29 numerical results suggest that while each of the addressed wireless solutions
30 does benefit from keeping people in the loop, the actual gains for every system
31 profile depend on the flexibility of the underlying access protocol. At the same
32 time, the costs associated with involving the human context may include certain
33 incentivization-related expenditures. These \ may vary a lot in the envisaged
34 heterogeneous, multi-tenant deployments, which calls for careful planning of
35 user engagement in future people-centric IoT infrastructure. Ultimately, the
36 rapidly maturing human-aware IoT ecosystem may become a new global utility,
37 thus “disappearing” in the “fabric of everyday life [15], while enabling a plethora
38 of next-generation applications and services.
39
40

41 Acknowledgment

42
43 The authors are particularly grateful to Yngve Selen (Wireless Access Networks
44 Department, Ericsson Research) for the insightful comments that allowed to
45 improve this paper.
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60